Validate Print Help

Percentage BoQ

Tender Inviting Authority: S.O(Civil), Rajrappa Area

Name of Work :-Repairing of light vehicle building under Rajrappa washery Project.

		Category of Bidder(To Be Selected by Bidder)	To Be Entered by Department		
ITC Not Available	Works Contract	Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :		Select	18.00	0.00	0.00

PRICE SCHEDULE (This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)

NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
SI. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	5	6	7
1	Providing corrugated G.S. sheet roofing including vertical/curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purins, rafters and trusses and including cutting to size and shape wherever required.0.63 mm thick with zinc coating not less than 275gm/ m ²	382.24	Sqm	821.25	313914.60	INR Three Lakh Thirteen Thousand Nine Hundred & Fourteen and Paise Sixty Only
2	Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of: Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of: G.S. Sheet	382.24	Sqm	97.70	37344.85	INR Thirty Seven Thousand Three Hundred & Forty Four and Paise Eighty Five Only
3	Extra for providing and fixing wind ties of 40x 6mm flat iron section.	240.00	m	138.75	33300.00	INR Thirty Three Thousand Three Hundred Only
4	Providing and fixing precoated galvanised steel sheet roofing accessories of total coated thickness 0.50mm (base metal of minimum 0.45mm thickness with total coating thickness of 0.05mm) with Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet	30.00	m	375.90	11277.00	INR Eleven Thousand Two Hundred & Seventy Seven Only
5	White washing with lime to give an even shade :old work (one or more coats)	379.26	Sqm	14.30	5423.42	INR Five Thousand Four Hundred & Twenty Three and Paise Forty Two Only
6	12 mm cement plaster of mix 1:6 (1 cement: 6 fine sand)	69.48	Sqm	217.70		INR Fifteen Thousand One Hundred & Twenty Five and Paise Eighty Only
7	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.One coat	642.67	Sqm	56.65		INR Thirty Six Thousand Four Hundred & Seven and Paise Twenty Six Only
8	Demolishing cement concrete manually by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)	2.55	Cum	1412.40	3601.62	INR Three Thousand Six Hundred & One and Paise Sixty Two Only
9	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry, but excluding the cost of nosing of steps etc. complete. 40mm thick with 20mm nominal size stone aggregate.	63.68	Sqm	452.50	28815.20	INR Twenty Eight Thousand Eight Hundred & Fifteen and Paise Twenty Only
10	Grading roof for water proofing treatment with Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	1.36	Cum	6616.35	8998.24	INR Eight Thousand Nine Hundred & Ninety Eight and Paise Twenty Four Only

Quoted Kate in Words		INR Zero Only				
Quoted Rate in Figures Quoted Rate in Words			Select		0.00	NR Zero Only
Total in Figures	tal in Figures					NR Six Lakh Twelve Thousand Three Hundred & leven and Paise Three Only
17	Total impact of GST for the purpose of CTC	1.000	Nos	0.00	0.00	NR Zero Only
16	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work.	9.07	Sqm	99.90	906.09	NR Nine Hundred & Six and Paise Nine Only
15	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. Fixed to steel windows by welding.	80.60	Kg	145.60		NR Eleven Thousand Seven Hundred & Thirty Five nd Paise Thirty Six Only
14	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6mm angle iron and 3mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using flats 30x6mm for diagonal braces and central cross piece.	6.03	Sqm	3730.40		NR Twenty Two Thousand Four Hundred & Ninety our and Paise Thirty One Only
13	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	74.06	Kg	92.55		NR Six Thousand Eight Hundred & Fifty Four and aise Twenty Five Only
12	Brick work with common burnt elay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1.6 (1 cement : 6 coarse sand)	9.38	Cum	6494.75		NR Sixty Thousand Nine Hundred & Twenty and aise Seventy Six Only
11	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer, 3 mm thick water proofing membrane, black finished reinforced with glass fibre matt consisting of a cost of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufactured of density at 25°C, 0.87 - 0.89 kg/litre and viscocity 70 - 160 cps. Over the primer coat the layer of membrane shall be laid using butane torch and sealing all joints etc., and preparing the surface complet. The visit physical and chemical parameters of the membrane shall be as under : Joint strength in longitudinal and transverse direction at 25°C as 530300 N/5 cm. Tear strength in longitudinal and transverse direction at 25°C as 500300 N/5 cm. Tear strength in longitudinal and transverse direction at 25°C as 530300 N/5 cm. Tear strength in longitudinal and transverse direction as 60/800N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane : 3 mm thick	34.24	Sqm	443.70		NR Fifteen Thousand One Hundred & Ninety Two and laise Twenty Nine Only