

| Tender Inviting Authority: Staff Officer (Civil),CCL, Giridih Area | | | | | |
|---|--|---|-----------------------------|-----------------------------------|---|
| Name of Work: provisioning of well equipped cabins at Entry & Exit point of mine with proper arrangement to fix RFID & Boom barrier under Giridih OCP under Giridih Area | | | | | |
| | Category of Services (To Be Selected by Department) | Category of Bidder(To Be Selected by Bidder) | To Be Entered by Department | | |
| ITC Not Available | Works Contract | Bidder's Status (Mandatory) | Rate of GST (in %) | GST to be Paid By Bidder (in Rs.) | GST to be Paid By CIL/Subsidiary (in Rs.) |
| Name of the Bidder/ Bidding Firm / Company : | | Select | 18.00 | 0.00 | 0.00 |
| PRICE SCHEDULE | | | | | |
| (This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only) | | | | | |
| NUMBER # | TEXT # | NUMBER # | TEXT # | NUMBER | NUMBER # |
| Sl. No. | Item Description | Quantity | Units | Estimated Rate in Rs. P | TOTAL AMOUNT in Rs. P |
| 1 | 2 | 3 | 4 | 5 | 7 |
| 1 | Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. 2.8.1 All kinds of soil | 9.15 | cum | 188.45 | 1724.32 |
| 2 | Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete | 1.65 | cum | 1,844.00 | 3042.60 |
| 3 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources | 2.03 | cum | 5,167.75 | 10490.53 |
| 4 | Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand) | 6.30 | cum | 5,322.15 | 33529.55 |
| 5 | Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 5.1.2 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources) | 1.30 | cum | 7,365.50 | 9575.15 |
| 6 | Lintels, beams, plinth beams, girders, bressumers and cantilevers | 10.38 | sqm | 470.70 | 4885.87 |
| 7 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more. | 103.78 | kg | 75.85 | 7871.71 |
| 8 | Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m | 8.46 | cum | 114.40 | 967.82 |
| 9 | Designing, providing, installing and fixing factory finished custom designed cold form Light Gauge Steel Framed super structure comprising of steel wall panel, trusses, purlins etc manufactured out of minimum 0.75 mm thick steel sheet as per design requirements. The steel sheet shall be galvanized (A2, 150gms Aluminium Zinc Alloy coated steel having minimum yield strength 300-550 Mpa) conforming to AISI specifications and IBC 2009 for cold formed steel framing and construction and also as per IS: 875-1987, ISO 800-1984 and IS-801-1975. The wind load shall be as per provisions of IS 875 (part -III). LGSFS frame shall be designed as per IS: 801 using commercially available software such as Frame CAD Pro-11.7/ STAAD PRO-V8i/ArchitektV2.5.16/ Revit architecture-2011 or equivalent. Proper usage of Connection Accessories like Heavy Duty Tension Ties, Light Duty Hold-ons, Twist Straps (to connect truss with wall frames), Strong Tie, Tie Rod, H-Brackets, Boxing Sections, L-Shaped Angles for better structural stability. The framing section shall be cold form C-type having minimum web depth 89 mm x 30mm flange x 11mm lip in required length as per structural design requirement duly punched with dimple/slot at required locations as per approved drawings. The slots will be along centre line of webs | 791.45 | kg | 199.10 | 157577.70 |
| 10 | Providing and fixing of external wall system on Light gauge steel frame work with outer face cement boards as per standard sizes fixed with self- drilling / tapping screws / fasteners @ 60cm c/c of approved make. A groove of 2 mm to 3mm shall be maintained and grooves shall be sealed with silicon based sealant. The board shall be fixed in a staggered pattern. Screws shall be of counter sunk rib head of 1.60mm to 4 mm thick or 8 to 10 gauge of length varying from 25 to 45 mm and. Internal face 12.5 mm thick gypsum plaster board fixed on cement board as per standard sizes fixed with self- drilling / tapping screws / fasteners @ 60cm c/c of approved make, proper taping and jointing to be done using fiber mesh tape and epoxy and acrylic based jointing compound for seamless finish.(cost of frame work to be paid for separately) 26.42.1 Outer face: Outer face having 6mm thick fiber cement board fixed on 9mm thick fiber cement board, Type A, as per IS:14862-2000 (high pressure steam cured) Inner Face :- 12.5 mm thick gypsum plaster board conforming to IS 2095:2011 fixed on 8 mm thick fibre cement board conforming to IS:14862:2000 of type B (High pressure steam cured) | 101.17 | sqm | 2,803.15 | 283594.69 |
| 11 | Providing and fixing in position, 230mm thick factory made Expanded Polystyrene Core (EPS Core) roof/floor panels made of 3 mm dia G.I. wire mesh with 50 mm pitch in both the directions and on both faces of panel, kept at 120 135 mm gap and connected by the zig zag G.I. wire of 3 mm dia at alternate row by welding (at an angle ranging from 50-70 degree). The EPS core shall consist of 100 mm thick EPS of density not less than 20kg/ per cum. The bottom side of the panel shall be finished by applying a layer of 60-65 mm thick cement mortar 1: 3 (1 cement: 3 coarse sand (not having more than 40% stone chips of size upto 6 mm)) A with the help of shotcreting equipment etc at a pressure of not less than 1 bar (100K/m2) and surface finished with trowel. The top face of the panel shall be provided and finished by applying 70-75 mm thick layer of cement 2121 SUB HEAD : 26- NEW TECHNOLOGIES AND MATERIALS concrete 1:1.5: 3 (1 cement :1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size). Fixing operations of roof/floor panels shall be completed in all respect as per drawings and specifications and under the overall direction of the Engineer-in-charge | 27.01 | sqm | 3,662.40 | 98921.42 |
| 12 | Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete as per the direction of Engineer-in-charge. | 18.58 | sqm | 752.85 | 13987.95 |
| 13 | Providing and laying gang saw cut 18 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1:cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete as per direction of Engineer-in-Charge. 16.86.1 With granite stone of area less than 0.50 sqm. | 14.97 | sqm | 3,466.35 | 51891.26 |
| 14 | Construction of cement concrete kerb with top and bottom width 115 and 165 mm respectively, 250 mm high in M 20 grade PCC on M-10 grade foundation 150 mm thick, foundation having 50 mm projection beyond kerb stone, kerb stone laid with kerb laying machine, foundation concrete laid manually, all complete as per clause 408 | 37.62 | m | 345.00 | 12978.90 |

| | | | | | | |
|-------------------------------|--|----------------------|--------|----------|-------------------|---|
| 15 | Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long drv wall screws @ 230 mm interval, including fixing of gypsum board to ceiling | 14.97 | sqm | 1,037.85 | 15536.61 | INR Fifteen Thousand Five Hundred & Thirty Six and Paise Sixty One Only |
| 16 | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately) : 21.1.1 For fixed portion 21.1.1.1 Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) | 44.82 | kg | 367.10 | 16453.42 | INR Sixteen Thousand Four Hundred & Fifty Three and Paise Forty Two Only |
| 17 | For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) 21.1.2.1 Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15 | 35.47 | kg | 434.00 | 15393.98 | INR Fifteen Thousand Three Hundred & Ninety Three and Paise Ninety Eight Only |
| 18 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): 5 mm thick float glass | 17.98 | sqm | 1,090.10 | 19600.00 | INR Nineteen Thousand Five Hundred & Ninety Nine and Paise One Hundred Only |
| 19 | Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge | 3.88 | sqm | 789.70 | 3064.04 | INR Three Thousand & Sixty Four and Paise Four Only |
| 20 | Supplying and installation of delineators (road way indicators, hazard markers, object markers), 80-100 cm high above ground level, painted black and white in 15 cm wide strips, fitted with 80 x 100 mm rectangular or 75 mm dia circular reflectorised panels at the top, buried or pressed into the ground and conforming to IRC-79 and the drawings. | 40.00 | nos. | 821.00 | 32840.00 | INR Thirty Two Thousand Eight Hundred & Forty Only |
| 21 | Provision of rumble strips | 27.00 | m | 2,000.00 | 54000.00 | INR Fifty Four Thousand Only |
| 22 | Providing and laying factory made chamfered edge Cement Concrete paver blocks in footpath, parks, lawns, drive ways or light traffic parking etc, of required strength, thickness & size/ shape, made by table vibratory method using PU mould, laid in required colour & pattern over 50mm thick compacted bed of sand, compacting and proper embedding/laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand. complete all as per direction of Engineer-in-Charge. 80 mm thick C.C. paver block of M-30 grade with approved color design and pattern. | 250.00 | sqm | 805.10 | 201275.00 | INR Two Lakh One Thousand Two Hundred & Seventy Five Only |
| 23 | Total impact of GST for the purpose of CTC | 1.000 | Nos | 0.00 | 0.00 | INR Zero Only |
| Total in Figures | | | | | 1049202.52 | INR Ten Lakh Forty Nine Thousand Two Hundred & Two and Paise Fifty Two Only |
| Quoted Rate in Figures | | | Select | | 0.00 | INR Zero Only |
| Quoted Rate in Words | | INR Zero Only | | | | |