

Validate Print Help Percentage BoQ						
Tender Inviting Authority: PE (Civil) Kargali OCP						
Name of Work: Repairing of Murti Memorial public School under Kargali OCP, BnK Area						
.	Category of Services (To Be Selected by Department)	Category of Bidder(To Be Selected by Bidder)	To Be Entered by Department			
ITC Not Available	Works Contract	Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)	
Name of the Bidder/ Bidding Firm / Company :		Select	18.00	0.00	0.00	
PRICE SCHEDULE (This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)						
NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	5	6	7
1	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	964.800	Kg	92.55	89292.24	INR Eighty Nine Thousand Two Hundred & Ninety Two and Paise Twenty Four Only
2	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer, 3 mm thick water proofing membrane, black finished reinforced with glass fibre matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufactured of density at 25°C, 0.87 - 0.89 kg/litre and visococity 70 - 160 cps. Over the primer coat the layer of membrane shall be laid using butane torch and sealing all joints etc., and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under : Joint strength in longitudinal and transverse direction at 23°C as 350/300 N/5 cm. Tear strength in longitudinal and transverse direction as 60/80N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane : 3 mm thick	98.000	Sqm	443.70	43482.60	INR Forty Three Thousand Four Hundred & Eighty Two and Paise Sixty Only
3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge.	4.990	Cum	2060.50	10281.90	INR Ten Thousand Two Hundred & Eighty One and Paise Ninety Only
4	Providing high impec Polypropylene reinforced by organic fibres and/or inorganic synthetic fibres cement 6 mm thick corrugated sheets (as per IS: 14871) roofing up to any pitch and fixing with polymer coated J, or L hooks, bolts and nuts 8 mm dia.G.I plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete (excluding the cost of purlins, rafters and trusses), including cutting sheets to size and shape wherever required.	56.500	Sqm	389.10	21984.15	INR Twenty One Thousand Nine Hundred & Eighty Four and Paise Fifteen Only
5	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 5.0 in foundation and plinth in:Cement mortar 1:6 (1 cement : 6 coarse sand)	2.030	cum	5322.15	10803.96	INR Ten Thousand Eight Hundred & Three and Paise Ninety Six Only
6	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and rammingof bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	3.870	cum	188.45	729.30	INR Seven Hundred & Twenty Nine and Paise Thirty Only
7	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6(1 cement: 6 coarse sand)	10.070	cum	6494.75	65402.13	INR Sixty Five Thousand Four Hundred & Two and Paise Thirteen Only
8	6 mm cement plaster of mix : 1:3 (1 cement : 3 fine sand)	83.390	Sqm	195.85	16331.93	INR Sixteen Thousand Three Hundred & Thirty One and Paise Ninety Three Only
9	12 mm cement plaster of mix :1:6 (1 cement: 6 fine sand)	153.540	Sqm	217.70	33425.66	INR Thirty Three Thousand Four Hundred & Twenty Five and Paise Sixty Six Only
10	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete.40 mm thick with 20 mm nominal size stone aggregate	19.570	Sqm	452.50	8855.43	INR Eight Thousand Eight Hundred & Fifty Five and Paise Forty Two Only
11	Distemping with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound) content less than 50 gram/ litre, of approved brand and of required said and colour complete to give and even said.Old work (one or more coats)	95.640	sqm	38.55	3686.92	INR Three Thousand Six Hundred & Eighty Six and Paise Ninety Two Only