Validate	Print	Help	Item Rate Boo
----------	-------	------	---------------

from natural sources)

Validate	Print Help		item Rate BoQ			
Tender Inviting Auth	ority:					
Name of the Work / Contract No:	Painting /Writing Safety Rule_Slogan on Exsiting MS Board and Mak East & West Quarry Under Sayal-OCP	Making 2 Nos Traffic Rule New Display Board for				
	Category of Services (To Be Selected by Department)		Category of Bidder ( To Be Selected by Bidder)			
ITC Available	Works Contract		Bidder's Status (Mandatory)	Total GST(in Rs.)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :			Select	0.00	0.00	0.00
(This BOQ template	must not be modified/replaced by the bidder and the same should be up	loaded after filli	PRICE SCHEDULE ng the relevent columns, else the	bidder is liable to be rej	ected for this tender. Bidders are a	allowed to enter the Bidder Name and Values only
NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER #	NUMBER #	TEXT #
SI. No.	Item Description	Quantity	Units	BASIC RATE In Figures To be entered by the Bidder in Rs. P	TOTAL AMOUNT Without Taxes in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	6	7	8
1	Part -A (Painting/Writing On Exisiting MS Board) Finishing with Epoxy paint (two or more coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete.  On steel work	1249.00	Sqmtr		0.00	INR Zero Only
2	Lettering with black Japan paint of approved brand and manufacture		per letter per cm height		0.00	INR Zero Only
3	Excavation work by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drains (not exceeding 1.5m in width or10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directed, within a lead of 50 m.Ordinary rock	9	Cum		0.00	INR Zero Only
4	1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural	9	Cum		0.00	INR Zero Only

Cum

9

5					0.00	INR Zero Only
	Part -B (Traffic Rule Retro Radium Board ) Size - 3 Mtr x 2 Mtr= 02 Nos Board Manufacturing, supplying and fixing retro reflective overhead signage boards made up of 2 mm thick aluminium sheet, face to be fully covered with high intensity and encapsulated lens type heat activated retro reflective sheeting conforming to type - III of ASTM-D-4956-01 as approved by Engineer-in-charge, letters, borders etc. as per IRC : 67-2001 in silver white with blue colour back ground and with high intensity grade, pasted on substrate by pressure sensitive adhesive backing which shall be activated by applying pressure conforming to class II of ASTM-D-4956-01 and fixing the same to the plate of structural frame work by means of suitable sized aluminium alloys, rivets or bolts & nuts@ 300 mm centre to centre all along the periphery as well as in two vertical rows along with theft resistant measures, including the cost of painting with two or more coats of epoxy paint in grey colour on the back side of aluminium sheet including appropriate priming coat. The rate includes the cost of rounding off the corners, lowering down the structural frame work from the gantry, fixing and erecting the same inposition all complete as per drawings, specification and direction of the engineer-in-charge. (Structural frame work including M.S. plate to be provided separately. Rectangular area of the sheet only shall be measured for payment). Size 2.5Mtr x 1.88 = Say 5Mtr x 2	12	Sqmtr			
6	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	412	Kg		0.00	INR Zero Only
7	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc. External work 80mm dia	56.5	Mtr		0.00	INR Zero Only
8	Excavation work by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drains (not exceeding 1.5m in width or10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directed, within a lead of 50 m.Ordinary rock	3	Cum		0.00	INR Zero Only
9	1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources)	3	Cum		0.00	INR Zero Only
10	Total impact of GST for the purpose of CTC	1.000	No.	0.00	0.00	INR Zero Only
Total in Figures			<u>I</u>		0.00	INR Zero Only
Quoted Rate in Word	its			INF	R Zero Only	