

Tender Inviting Authority: HOD (MM-Purchase), Central Coalfields Limited

Name of Work: Pre-NIT for Procurement of various types of Engineering Wire Ropes

Tender Ref No: CCL/CM(Pur)/Pre-NIT/Engg. Wire Ropes/2022

Bidder Name :		GST REGISTRATION NO.:	
---------------	--	-----------------------	--

PRICE SCHEDULE

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values/Percentage only)

NUMBER #	TEXT #	TEXT #	NUMBER #	TEXT #	TEXT #	NUMBER #	Percentage	NUMBER	NUMBER	NUMBER	NUMBER	TEXT	TEXT	Percentage	Percentage	NUMBER	Percentage	TEXT	NUMBER #	NUMBER #	TEXT #
Sl. No.	Item Description	Item Code / Make	Quantity	Unit of Measurement	Quoted Currency in INR / Other Currency	PER UNIT BASIC RATE in Figures To be entered by the Bidder (in Rs.)	Discount (in %)	Packing & Forwarding (in Rs.)	Freight Charges (Rs.) Excl. Of GST	Transit Insurance Excl. Of GST	Installation, Commissioning & Training charges (if any) per Unit [Column 5]	Sub-Total	GST/ Opted For Composition Levy.	Rate Of GST (in %)	Value of GST (Rs)	Less For Input Tax Credit on account of GST (RS)	HSN Code for the item	TOTAL AMOUNT With Taxes etc. (All Inclusive)	Cost to CCL (Landed rate after availing credit of applicable taxes/ duties etc.)- Rate for deciding L-1	TOTAL AMOUNT In Words	
1	2	3	4	5	12	13	14	15	22	23	24	25	26	27	28	29	30	53	54	55	
1	Hoist Rope suitable for WK12C Electric Rope Shovel:- dia- 60.5 mm, Construction: 6X36SW, Length: 79.5m, Coating: Ungalvanised with Plastic Impregnated Core, IWR Ray, RHL, Tenale Strength: 1770 Mpa Lube Type: No need, Standard: IS 13917 : 2003 or ISO 3154, End Fitting (i.e. Socket). Both ends of the rope should have Swaged round Sleeve/Button type preparation with smaller rope for pulling purpose(Dimension of sleeve: OD:87.5mm, Height: 107 mm), (As per TZ Shovel P.No. K1423.05.01).	item1	954	Mtr.	INR							0.00	Select		0.00	0.00		0.0000	0.0000	INR Zero Only	
2	Suspension Cable- dia- 60.5mm, Construction:DF8X37F + IWRC (Compacted), Length: 11.54m, Un-galvanised, covered with Impregnated PVC Core IWRC, STD Ray, RHL, Tenale Strength: 1470 Mpa, the broken wire exceed 7% in one untwist, Standard: IS 2266:2019 or EN 12385-4, Lube Type: No need, End Fitting: Femule (as per TZ shovel P. No.: K1429.10.12.00) with Minimum Breaking Load= 2000 KN.	item2	92.32	Mtr.	INR							0.00	Select		0.00	0.00		0.0000	0.0000	INR Zero Only	
3	Hoist Rope for Escort RT 20/30, TIL 30T Crane - Dia of rope 16mm, 19x7 Construction, Non - Rotating, Preformed, 1960 N / sq mm, RHO, WSC, Ungalvanised, MBL-165 Kn, Length - 170 meters, As per IS: 2266 / 2002, (End to be fused and sealed)	item3	680	Mtr.	INR							0.00	Select		0.00	0.00		0.0000	0.0000	INR Zero Only	