Validate	Print Help Percentage E	<u>BoQ</u>				
Tender Inviting Author	ority: Staff Officer (Civil),CCL, Dhori Area					
Name of Work:-R/M o	of 10 nos Qtr(DK/149,150,152,06,10,02,120,260,116,04) at Dhori Khas colliery					
	Category of Services (To Be Selected by Department)		Category of Bidder( To Be Selected by Bidder)	To Be Entered by Department		
ITC Not Available	Works Contract		Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :			Select	18.00	0.00	0.00
(This BOQ tem	plate must not be modified/replaced by the bidder and the same should be up	loaded after filling	PRICE SCHEDULE g the relevent columns, else the	bidder is liable to be rejected for thi	is tender. Bidders are allo	owed to enter the Bidder Name and Values only )
(This BOQ temp	plate must not be modified/replaced by the bidder and the same should be up	oloaded after filling		bidder is liable to be rejected for thi	is tender. Bidders are alle	owed to enter the Bidder Name and Values only )  TEXT #
,			g the relevent columns, else the	· · · · · · · · · · · · · · · · · · ·		
NUMBER#	TEXT#	NUMBER#	g the relevent columns, else the	NUMBER Estimated Rate in	NUMBER#  TOTAL AMOUNT in  Rs. P	TEXT # TOTAL AMOUNT in Words
NUMBER # SI. No.	TEXT #  Item Description	NUMBER # Quantity	g the relevent columns, else the TEXT # Units	NUMBER Estimated Rate in Rs. P	NUMBER#  TOTAL AMOUNT in  Rs. P	TEXT # TOTAL AMOUNT in Words

3	Providing & fixing to existing door frames: 30mm thick factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19mm x 19mm for styles and 15x15mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5mm thick heat moulded PVC 'C' channel of size 30mm thickness, 70mm width out of which 50mm shall be flat and 20mm shall be tapered in 45degree angle on either side forming styles; and 5mm thick, 95mm wide PVC sheet out of which 75mm shall be flat and 20mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115mm wide PVC sheet out of which 75mm shall be flat and 20mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided either side of the panel. 10mm (5mm x 2 ) thick, 20mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail. paneling of 5mm thick both side PVC sheet to be fitted in the M.S. frame welded/sealed to the styles & rails with 7mm (5mm+2mm) thick x 15mm wide PVC sheet beading on inner side, and joined together with solvent cement	31.08	sqm	2092.3		INR Sixty Five Thousand &Twenty Eight and Paise Sixty Eight Only
4	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	475.34	sqm	452.5	215091.35	INR Two Lakh Fifteen Thousand &Ninety One and Paise Thirty Five Only
5	Distempering with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound ) content less than 50 gram/ litre, of approved brand and of required said and colour complete to give and even said : Old work (one or more coats)	1920	sqm	38.55	74016.00	INR Seventy Four Thousand &Sixteen Only
6	Painting with synthetic enamel paint of approved brand & manufacturer of required Colour to give an even shade. One or more coats on old work.	456	sqm	65.65	29936.40	INR Twenty Nine Thousand Nine Hundred & Thirty Six and Paise Forty Only
7	Colour washing such as green, blue or buff to give an even shade: New work (two or more coats) with a base coat of white washing with lime.	2240	sqm	33.4		INR Seventy Four Thousand Eight Hundred & Sixteen Only
8	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	12000	ltrs	8.4	100800.00	INR One Lakh Eight Hundred Only

Providing and fining varier closer squarting pain (indian type W.C. pain) with 120m manufacture of closer squarting cattern with namenal controlled device (funded sweet) individual cattern and making pain the wash and fallows wherever required i white Vireaus clinia of loss pattern W.C. pain of size 500 x 400mm with integral type foot rests.  10 Providing and fining 15' quality coramic glazed wall tiles conforming to it is 15.022 (thickness to be specified by the manufacture) of approved make in all colours, basheds cregit brigging of the conforming to it is 15.022 (thickness to be specified by the manufacture) of approved make in all colours, basheds cregit brigging of the conforming the colours of the conforming to the colours of						
to IS : 15822 (thickness to be specified by the manufacture) or approved make in all colours, shade sexpt burgundy, bottle green, black of any size as approved by Engineer-Iff charge) in skirting, risers of steps and dadso over 12mm tick bed of cement morat 13 (1 cement 3 coarse sand) and jointing with grey cement sturry & 3.38 per sign including pointing in white cement mixed with pigment of matching shade complete.  11 Providing and laying ceramic glazed floor tiles 300 x 300mm (thickness to be specified by the manufacture) of 2 valualty conforming to 5: 15622 of approved make in colours such as white, lover, Grey, Fune, Red Brown, laid on 20mm thick cement morat 12 (1 cement at coarse sand) including pointing the joints with white cement and matching pigment etc. complete.  12 Providing and fixing Chlorinated Polyvinyl chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plan & This includes jointing of pipes complete as per direction of the fingheer-incharge: 2 Team nominal outer do pipes.  13 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plan & This includes jointing of pipes complete as per direction of the fingheer-incharge: 2 Team nominal outer do pipes.  13 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot 8. Old water supply, including all CPVC plan & This includes jointing of pipes complete as per direction of the fingheer-incharge: 2 Team nominal outer do pipes.  14 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot 8. Old water supply, including all CPVC pipes, having thermal stability for hot 8. Old water supply, including all CPVC pipes, having thermal stability for hot 8. Old water supply including all CPVC pipes, having thermal stability for hot 8. Old water supply including all CPVC pipes, having thermal stability for hot 8. Old water supply including all CPVC pipes,	9	PVC flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete including cutting and making good the walls and floors wherever required: White Vitreous china Orissa pattern W.C. pan of size 580 x	12	nos	4774.45	57293.40 INR Fifty Seven Thousand Two Hundred & Ninety Three and Paise Fαrty Only
x 300mm (thickness to be specified by the manufacturer) of 1" quality conforming to 15: 15622 of approved make in colours such as white, lown, Grey, Fume, Red Brown, laid on 20mm thick cement mortar 14: (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc. complete.  12 Providing and fixing Chlorinated Polyvinyl chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC poline & the cramps at 1.00 m spacing. This includes jointing of pipes complete as per direction of the Engineer-incharge. 25mm nominal outer dia pipes.  13 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC poline & the space of direction of the Engineer-incharge. 25mm nominal outer dia pipes.  13 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC poline Makes sthreaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes with clamps at 1.00 m spacing. This includes jointing of pipes with clamps at 1.00 m spacing. This includes jointing of pipes a fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. 20 mm nominal outer dia Pipes  14 Providing and fixing brass bib cock of approved quality: 15 mm nominal bore  15 Izmm cement plaster of mix 1.6 (1. cement: 6 fine sand).  360 Sqm 21.7.7  7837.200 NR Seventy Eight Thousand Three Hundred & Seventy Two Only Two Only	10	to IS: 15622 (thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-Ifr charge) in skirting, risers of steps and dados over 12mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with	151.2	sqm	871.3	131740.56 INR One Lakh Thirty One Thousand Seven Hundred & Forty and Paise Fifty Six Only
having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings including fixing the pipe with clamps at 1.00 m spacing. This includes plointing of pipes complete as per direction of the Engineer-incharge. : 25mm nominal outer dia pipes.  13 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, havingthermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of pipes & fittings with one step CPVC solvent cement and testing of pipes & fittings with one step CPVC solvent cement and testing of pipes and pipes aper direction of Engineer in Charge. 20 mm nominal outer dia Pipes  14 Providing and fixing brass bib cock of approved quality: 15 mm nominal bore  15 12mm cement plaster of mix 1:6 (1. cement: 6 fine sand).  16 12 mm cement plaster finished with a floating coat of neat cement  1785.00 INR Seventeen Thousand Elighty Five Only	11	x 300mm (thickness to be specified by the manufacturer) of 1" quality conforming to IS: 15622 of approved make in colours such as white, Ivory, Grey, Fume, Red Brown, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc.	32.4	sqm	762.8	
havingthermal stability for hot & cold water supply, including all CPVC plain &brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. 20 mm nominal outer dia Pipes  14 Providing and fixing brass bib cock of approved quality: 15 mm nominal bore  15 Providing and fixing brass bib cock of approved quality: 15 mm nominal bore  16 12 mm cement plaster of mix 1:6 (1. cement: 6 fine sand).  18 mtrs  259.05  Ninety Only  Ninety Only  Ninety Only  18 mtrs  259.05  Ninety Only  18 Seventy Eight Thousand Four Hundred & Ninety Five Only  Two Only  18 mtrs  259.05  Ninety Only  18 mtrs  259.05  Ninety Only  18 mtrs  259.05  Ninety Only	12	having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes complete as per direction of the Engineer-incharge.: 25mm nominal outer dia	14.4	mtrs	331.5	
nominal bore 36 nos 263.75  12mm cement plaster of mix 1:6 (1. cement : 6 fine sand).  360 sqm 217.7  16 12 mm cement plaster finished with a floating coat of neat cement  17085.00 INR Seventeen Thousand & Eighty Five Only	13	havingthermal stability for hot & cold water supply, including all CPVC plain &brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as	18	mtrs	259.05	
360 sqm 217.7 Two Only  16 12 mm cement plaster finished with a floating coat of neat cement  17085.00 INR Seventeen Thousand & Eighty Five Only	14		36	nos	263.75	9495.00 INR Nine Thousand Four Hundred & Ninety Five Only
12 min cement plaster missied with a nothing coat of neat cement	15	12mm cement plaster of mix 1:6 (1. cement : 6 fine sand).	360	sqm	217.7	
	16	· · · · · · · · · · · · · · · · · · ·	60	sqm	284.75	17085.00 INR Seventeen Thousand &Eighty Five Only

Quoted Rate in Words		Select INR Zero Only				
Quoted Rate in Figures			0.1		0.00	INR Zero Only
Total in Figures					1340492.85	INR Thirteen Lakh Forty Thousand Four Hundred & Ninety Two and Paise Eighty Five Only
19	Total impact of GST for the purpose of CTC	1.000	Nos	0.00		INR Zero Only
18	Brick work with common burnt clay F.P.S.(non modular) bricks of class designation 5.0 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1 cement : 6 coarse sand).		cum	6494.75		INR Thirty Eight Thousand Nine Hundred & Sixty Eight and Paise Fifty Only
17	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 5.0 in foundation and plinth in : Cement mortar 1:6 (1 cement : 6 coarse sand).		cum	5322.15		INR Forty Two Thousand Five Hundred & Seventy Seven and Paise Twenty Only