Validate	Print Help Percentage BoQ				
Tender Inviting Autho	rity:STAFF OFFICER CIVIL				
Name of Work: Repair	and Renovation of Personnel Office and Provision of Kali Temple in place of	of existing damaged one with bo	undary wall and other al	lied works at TNOCP of H	azaribagh Area
		Category of Bidder( To Be Selected by Bidder)	To Be Entered by Department		
ITC Available	Works Contract	Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :		Select	18.00	0.00	0.0

## PRICE SCHEDULE

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )

NUMBER #	TEXT #	NUMBER#	TEXT #	NUMBER	NUMBER#	TEXT #
SI. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	5	6	7
1	Item Description/ Heading					
1.01	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1 cement : 6 coarse sand)	65.25	Cum	6494.75	423782.44	INR Four Lakh Twenty Three Thousand Seven Hundred & Eighty Two and Paise Forty Four Only
1.02	Supplying and filling in plinth with Jamuna sand under floors, including watering, ramming, consolidating and dressing complete.	8.13	Cum	1844.00	14991.72	INR Fourteen Thousand Nine Hundred & Ninety One and Paise Seventy Two Only
1.03	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:3:6 (1 Cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).	14.92	Cum	5916.00	88266.72	INR Eighty Eight Thousand Two Hundred & Sixty Six and Paise Seventy Two Only
1.04	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand)	64.36	Cum	5322.15	342533.57	INR Three Lakh Forty Two Thousand Five Hundred & Thirty Three and Paise Fifty Seven Only
1.05	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1 cement : 6 coarse sand)	37.70	Cum	6494.75	244852.08	INR Two Lakh Forty Four Thousand Eight Hundred & Fifty Two and Paise Eight Only
1.06	Providing and laying damp-proof course 40mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 12.5mm nominal size).	13.00	Sqm	318.65	4142.45	INR Four Thousand One Hundred & Forty Two and Paise Forty Five Only
1.07	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement, with 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size).	2.89	Cum	8797.65	25425.21	INR Twenty Five Thousand Four Hundred & Twenty Five and Paise Twenty One Only

1.00 Seed materiorement for ECC worth including simplement, soliting to soliting with plant of the soliting soliting in solition and soliting soliting in soliting soliting in soliting soliting in soliting soliting in soliting so							
1.00 monoual for two furthers, pointh bowns, griders, branches and freeze transcriptores.  1.10 silling analysis exceeded earth foundating rodal in treaches, patch, side of foundations on in livers and exceeded earth foundating rodal in treaches, patch, side of foundations on in livers and exceeded griders and the patch of the p	1.08	bending, placing in position and binding all complete up to plinth	231.20	Kg	75.85	17536.52	INR Seventeen Thousand Five Hundred & Thirty Six and Paise Fifty Two Only
1.10 also of Foundations et in layers not exceeding 20cm in eight, consolidating each of copiet all yet for yearming and watering, lead on 10 S /m and lift up to 12 m.  1.11 and an initial process of the company of the control of the company of t	1.09	removal of form for : Lintels, beams, plinth beams, girders,	24.24	Sqm	470.70	11409.77	INR Eleven Thousand Four Hundred & Nine and Paise Seventy Seven Only
1.11 connecting plate including cottoting, floring in position and applying a primary count of approved the plane at Complete. 1 45-24	1.10	sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up	50.97	Cum	114.40	5830.97	
shape and pitch of corrugation as approved by regineer-in-charge) 0.50 mm (+ 0.50 s) factor alored thinkness with incr coating 120 mp per sym as per \$5.277 in 20 mp as test grade, 5.7 microns epoxy primer on both side of the sheet and polyester top coat \$1.38 microns. Sheet should have protective guard film of 25 microns minimum to avoid scarches druing transportation and should be supplied in single length upot 12 meter or as desired by Engineer-in-charge. The sheet shall be food upon ger defining feel feelings acrossed of size \$5.35 mm] with PPOM seal, complete upon any pitch in horizontal Vertical covered without the special of the size of the	1.11	connecting plate including cutting, hoisting, fixing in position and	455.24	Kg	77.95	35485.96	
accessories 0.50 mm (+ 0.05 %) total coasted thickness, Zinc coating 120 grams per sym as per 15: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete: Ridges plain (500 - 600mm)  1.14  Extra for providing and fixing 18mm thick gang saw cut mirror polished premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size, approved shade, colour and texture laid over 20mm thick base cement mortar 1:4 (1 ement: 4 coarse sand) joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Raj Nagar Plain white marble/ ¿Zebra black marble. Area of slab upto 0.9.0 sqm.  1.16  1.17  1.18  1.19  1.19  1.10  1.10  1.10  1.11  1.11  1.12  1.12  1.15  1.15  1.15  1.16  1.16  1.17  1.17  1.18  1.18  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.10  1.10  1.10  1.11  1.12  1.13  1.14  1.15  1.	1.12	shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm ( + 0.05 %),total coated thickness with zinc coating 120 gm per sqm as per 15:277 in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever	97.75	Sqm	571.00	55815.25	INR Fifty Five Thousand Eight Hundred & Fifteen and Paise Twenty Five Only
Extra for providing and fixing wind ties of 40x 6mm flat iron section.  Providing and fixing 18mm thick gang saw cut mirror polished premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20mm thick base cement mortar 1.4 (1 cement : 4 coarse sand) joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Raj Nagar Plain white marble/ Udaipur green marble/ Zebra black marble. Area of slab upto 0.50 sqm.  1.16  1.2 mm cement plaster of mix 1:6 (1 cement: 6 fine sand) Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete  1.2.5 mm thick tapered edge gypsum plain board conforming to IS:	1.13	accessories 0.50 mm (+ 0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping	4.50	m	375.90	1691.55	INR One Thousand Six Hundred & Ninety One and Paise Fifty Five Only
premoulded and prepolished, machine cut for kitchen platforms, vanity counters, windows sills, facias and similar locations of required size, approved shade, colour and texture laid over 20mm thick base cement mortar 1.4 (1 cement: 4 coarse sand) joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Raj Nagar Plain white marble/ Udaipur green marble/ Zebra black marble. Area of slab upto 0.50 sqm.  1.16  1.2 mm cement plaster of mix 1:6 (1 cement: 6 fine sand)  Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete  1.17  1.18  1.19  1.19  1.10  1.10  1.10  1.11  1.11  1.12  1.12  1.13  1.14  1.15  1.15  1.15  1.15  1.16  1.17  1.17  1.18  1.19  1.19  1.19  1.19  1.10  1.10  1.10  1.11  1.11  1.12  1.12  1.13  1.14  1.15  1.15  1.15  1.15  1.15  1.16  1.17  1.17  1.18  1.19  1.19  1.19  1.19  1.10  1.10  1.10  1.11  1.12  1.12  1.13  1.14  1.15  1.15  1.15  1.15  1.15  1.15  1.15  1.15  1.16  1.17  1.17  1.17  1.18  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.19  1.10  1.10  1.11  1.12  1.12  1.13  1.14  1.15	1.14	Extra for providing and fixing wind ties of 40x 6mm flat iron section.	47.00	m	138.75	6521.25	
1.10 12 mm cement plaster of mix 1:6 (1 cement: 6 fine sand) 607.42 5qm 217.70 143297.33 Ninety Seven and Paise Thirty Three Only  Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete 667.42 5qm 98.45 65707.50 INR Sixty Five Thousand Seven Hundred & Seven and Paise Fifty Only Paise Fifty Only  12.5 mm thick tapered edge gypsum plain board conforming to IS: 61.00 609.65	1.15	premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size, approved shade, colour and texture laid over 20mm thick base cement mortar 1:4 (1 cement : 4 coarse sand) joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Raj Nagar Plain white marble/ Udaipur green marble/ Zebra black marble. Area of slab upto	74.50	Squar	2340.05	174333.73	INR One Lakh Seventy Four Thousand Three Hundred & Thirty Three and Paise Seventy Three Only
thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:  12.5 mm thick tapered edge gypsum plain board conforming to IS:	1.16	12 mm cement plaster of mix 1:6 (1 cement: 6 fine sand)	667.42	Sqm	217.70	145297.33	INR One Lakh Forty Five Thousand Two Hundred & Ninety Seven and Paise Thirty Three Only
1.18 12.5 mm thick tapered edge gypsum plain board conforming to IS: 61.50 Sqm 903.65 Sqm 903.65 S5574.48 INR Fifty Five Thousand Five Hundred & Seventy Four and Paise Forty Seven Only	1.17	thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth	667.42	Sqm	98.45		
	1.18		61.50	Sqm	903.65	55574.48	INR Fifty Five Thousand Five Hundred & Seventy Four and Paise Forty Seven Only

1.19	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	162.07	Kg	92.55	14999.58	INR Fourteen Thousand Nine Hundred & Ninety Nine and Paise Fifty Eight Only
1.20	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6mm angle iron and 3mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using flats 30x6mm for diagonal braces and central cross piece.	5.94	Sqm	3730.40	22158.58	INR Twenty Two Thousand One Hundred & Fifty Eight and Paise Fifty Eight Only
1.21	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size, with top and bottom rail of T-iron 40x40x6mm, with 40mm dia steel pulleys, complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer	6.30	Sqm	7450.80	46940.04	INR Forty Six Thousand Nine Hundred & Forty and Paise Four Only
1.22	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade. New work (two or more coats) over and including water thinnable priming coat with cement primer.	251.28	Sqm	115.00	28897.20	INR Twenty Eight Thousand Eight Hundred & Ninety Seven and Paise Twenty Only
1.23	New work (Two or more coat applied @ 1.67 ILO 0 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sarM	477.64	Sqm	115.85	55334.59	INR Fifty Five Thousand Three Hundred & Thirty Four and Paise Fifty Nine Only
1.24	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work	147.95	Sqm	99.90	14780.21	INR Fourteen Thousand Seven Hundred & Eighty and Paise Twenty Only
1.25	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand, including finishing the top smooth	22.44	Sqm	551.30	12371.17	INR Twelve Thousand Three Hundred & Seventy One and Paise Seventeen Only
1.26	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer-in-charge	803.25	Sqm	752.85	604726.76	INR Six Lakh Four Thousand Seven Hundred & Twenty Six and Paise Seventy Six Only
1.27	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15 cm deep and disposal of rubbish, lead up to 50 m and lift upto 1.5 m. All kinds of soil.	803.25	Sqm	19.75	15864.19	INR Fifteen Thousand Eight Hundred & Sixty Four and Paise Nineteen Only
1.28	12 mm cement plaster of mix 1:6 (1 cement: 6 fine sand)	1221.22	Sqm	217.70	265859.59	INR Two Lakh Sixty Five Thousand Eight Hundred & Fifty Nine and Paise Fifty Nine Only
1.29	6 mm cement plaster of mix : 1:3 (1 cement: 3 fine sand)	219.66	Sqm	195.85	43020.41	INR Forty Three Thousand &Twenty and Paise Forty One Only
1.30	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	1043.80	Sqm	98.45	102762.11	INR One Lakh Two Thousand Seven Hundred & Sixty Two and Paise Eleven Only
1.31	P/A rustic paint	397.08	Sqm	250.39	99424.86	INR Ninety Nine Thousand Four Hundred & Twenty Four and Paise Eighty Six Only
1.32	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound ) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats	1043.80	Sqm	84.50	88201.10	INR Eighty Eight Thousand Two Hundred & One and Paise Ten Only
1.33	New work (Two or more coat applied @ 1.67 ILO 0 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sarM	397.08	Sqm	115.85	46001.72	Only
1.34	12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- Part I.	219.66	Sqm	903.65	198495.76	INR One Lakh Ninety Eight Thousand Four Hundred & Ninety Five and Paise Seventy Six Only

1.35	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately): For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	93.36	Кg	367.10	34272.46	INR Thirty Four Thousand Two Hundred & Seventy Two and Paise Forty Six Only
1.36	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	44.28	Kg	434.00	19217.52	INR Nineteen Thousand Two Hundred & Seventeen and Paise Fifty Two Only
1.37	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 4.0 mm thickness	26.24	Sqm	824.65	21638.82	INR Twenty One Thousand Six Hundred & Thirty Eight and Paise Eighty Two Only
1.38	Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws.	32.40	Sqm	2388.75	77395.50	INR Seventy Seven Thousand Three Hundred & Ninety Five and Paise Fifty Only
1.39	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	274.36	Kg	92.55	25392.02	INR Twenty Five Thousand Three Hundred & Ninety Two and Paise Two Only
1.40	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622 of approved make in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm	58.87	Sqm	1180.40	69490.15	INR Sixty Nine Thousand Four Hundred & Ninety and Paise Fifteen Only
1.41	Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer) with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make in all colours & shade in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1cement: 3 coarse sand), including grouting the joint with white cement &matching pigments etc. complete. Size of Tile 600x600 mm	38.63	Sqm	1221.20	47174.96	INR Forty Seven Thousand One Hundred & Seventy Four and Paise Ninety Six Only
1.42	Providing and fixing water closet squatting pan (Indian type W.C. pan ) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	2.00	No.	4774.45	9548.90	INR Nine Thousand Five Hundred & Forty Eight and Paise Ninety Only

11960.60 INR Eleven Thousand Nine Hundred & Sixty and Paise Sixty Only
4984.05 INR Four Thousand Nine Hundred & Eighty Four and Paise Five Only
2757.30 INR Two Thousand Seven Hundred & Fifty Seven and Paise Thirty Only
1342.20 INR One Thousand Three Hundred & Forty Two and Paise Twenty Only
252.00 INR Two Hundred & Fifty Two Only
1582.50 INR One Thousand Five Hundred & Eighty Two and Paise Fifty Only
2110.00 INR Two Thousand One Hundred & Ten Only
15543.00 INR Fifteen Thousand Five Hundred & Forty Three Only
3148.80 INR Three Thousand One Hundred & Forty Eight and Paise Eighty Only
1146.00 INR One Thousand One Hundred & Forty Six Only
20253.73 INR Twenty Thousand Two Hundred & Fifty Three and Paise Seventy Three Only
34288.96 INR Thirty Four Thousand Two Hundred & Eighty Eight and Paise Ninety Six Only
3284.25 INR Three Thousand Two Hundred & Eighty Four and Paise Twenty Five Only
30204.23 INR Thirty Thousand Two Hundred & Four and Paise Twenty Three Only

Quoted Rate in Words				INR	Zero Only	
oted Rate in Fig	ures		Select		0.00	INR Zero Only
tal in Figures						INR Thirty Eight Lakh Seventy Eight Thousand Seven Hundred & Thirty and Paise Eighty Six Only
2.00	Total impact of GST for the purpose of CTC	1.000	Nos	0.00	0.00	INR Zero Only
1.66	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.: Internal work - Exposed on wall 25 mm nominal outer dia .Pipes.	30.00	metre	331.50	9945.00	INR Nine Thousand Nine Hundred & Forty Five Only
1.65	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 25 mm nominal bore	2.00	No.	462.15	924.30	INR Nine Hundred & Twenty Four and Paise Thirty Or
1.64	IS:4992 with necessary screws etc. complete: 125 mm  Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank.	1500.00	Litre	8.40	12600.00	INR Twelve Thousand Six Hundred Only
1.63	Providing and fixing ISI marked oxidised M.S. handles conforming to	36.00	No.	29.85	1074.60	INR One Thousand &Seventy Four and Paise Sixty Only
1.62	Providing and fixing ISI marked oxidised M.S. tower bolt black finish, (Barrel type) with necessary screws etc. complete : 250x10 mm	36.00	No.	63.60	2289.60	INR Two Thousand Two Hundred & Eighty Nine and Paise Sixty Only
1.61	Providing and fixing ISI marked oxidised M.S. sliding door bolts with nuts and screws etc. complete : 300x16 mm	18.00	No.	153.75	2767.50	INR Two Thousand Seven Hundred & Sixty Seven ar Paise Fifty Only
1.60	Centering and shuttering including strutting, propping etc. and removal of form for: Lintels, beams, plinth beams, girders, bressumers and cantilevers	4.83	Sqm	470.70	2273.48	INR Two Thousand Two Hundred & Seventy Three a Paise Forty Eight Only
1.59	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete up to plinth level. Thermo-Mechanically Treated bars.	80.00	Кg	75.85	6068.00	INR Six Thousand &Sixty Eight Only
1.58	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement, with 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size).	1.00	Cum	8797.65	8797.65	INR Eight Thousand Seven Hundred & Ninety Seven and Paise Sixty Five Only
1.57	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand)	3.00	Cum	5322.15	15966.45	INR Fifteen Thousand Nine Hundred & Sixty Six and Paise Forty Five Only