

Validate		Print		Help		Percentage BoQ	
Tender Inviting Authority: PE (Civil) Kargali OCP							
Name of Work: R&M of community centre and renovation of bathroom at Jawahar nagar under Kargali OCP of B&K Area.							
Category of Services (To Be Selected by Department)		Category of Bidder(To Be Selected by Bidder)		To Be Entered by Department			
ITC Not Available	Works Contract	Bidder's Status (Mandatory)		Rate of GST (in %)		GST to be Paid By Bidder (in Rs.)	
Name of the Bidder/ Bidding Firm / Company :		Select		18.00		0.00	
<p align="center">PRICE SCHEDULE</p> <p align="center">(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)</p>							
NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #	
Sl. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words	
1	2	3	4	5	6	7	
1	(Part-A) Distemping with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound) content less than 50 gram/ litre, of approved brand and of required said and colour complete to give and even said.Old work (one or more coats)	668.070	Sqm	38.55	25754.10	INR Twenty Five Thousand Seven Hundred & Fifty Four and Paise Ten Only	
2	Finishing walls with water proofing cement paint of required shade :Old work (one or more coats applied @ 2.20 kg/10 sqm) over priming coat of primer applied @ 0.80 litrs/10 sqm complete including cost of Priming coat.	339.190	Sqm	72.30	24523.44	INR Twenty Four Thousand Five Hundred & Twenty Three and Paise Forty Four Only	
3	White washing with Satna lime wash on walls with one coat.	294.310	Sqm	9.85	2898.95	INR Two Thousand Eight Hundred & Ninety Eight and Paise Ninety Five Only	
4	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new work	104.630	Sqm	99.90	10452.54	INR Ten Thousand Four Hundred & Fifty Two and Paise Fifty Four Only	
5	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	100.000	Sqm	98.45	9845.00	INR Nine Thousand Eight Hundred & Forty Five Only	
6	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.Size of Tile 600x600 mm	72.640	Sqm	1180.40	85744.26	INR Eighty Five Thousand Seven Hundred & Forty Four and Paise Twenty Six Only	
7	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	39.300	Sqm	871.30	34242.09	INR Thirty Four Thousand Two Hundred & Forty Two and Paise Nine Only	
8	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer, 3 mm thick water proofing membrane, black finished reinforced with glass fibre matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufactured of density at 25°C, 0.87 - 0.89 kg/litre and viscosity 70 - 160 cps. Over the primer coat the layer of membrane shall be laid using butane torch and sealing all joints etc., and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under : Joint strength in longitudinal and transverse direction at 23°C as 350/300 N/5 cm. Tear strength in longitudinal and transverse direction as 60/80N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane : 3 mm thick	161.250	Sqm	443.70	71546.63	INR Seventy One Thousand Five Hundred & Forty Six and Paise Sixty Two Only	
9	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing I paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	18.000	Kg	367.10	6607.80	INR Six Thousand Six Hundred & Seven and Paise Eighty Only	

10	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing I paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron)	17.380	Kg	462.05	8030.43	INR Eight Thousand & Thirty and Paise Forty Three Only
11	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm.	6.140	Sqm	1090.10	6693.21	INR Six Thousand Six Hundred & Ninety Three and Paise Twenty One Only
12	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank.	2000.000	Leter	8.40	16800.00	INR Sixteen Thousand Eight Hundred Only
13	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar	2.090	cum	1194.45	2496.40	INR Two Thousand Four Hundred & Ninety Six and Paise Forty Only
14	Providing reinforced by organic fibres and/or inorganic synthetic fibres cement 6 mm thick corrugated sheets (as per IS: 14871) roofing up to any pitch and fixing with polymer coated J, or L hooks, bolts and nuts 8 mm dia.G.I. plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete (excluding the cost of purlins, rafters and trusses), including cutting sheets to size and shape wherever required.	54.130	Sqm	389.10	21061.98	INR Twenty One Thousand & Sixty One and Paise Ninety Eight Only
15	Dismantling roofing including ridges, hips, valleys and gutters etc., and Asbestos Cement sheet	54.130	Sqm	45.80	2479.15	INR Two Thousand Four Hundred & Seventy Nine and Paise Fifteen Only
16	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	9.450	Sqm	452.50	4276.13	INR Four Thousand Two Hundred & Seventy Six and Paise Twelve Only
17	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources)	9.600	cum	6490.90	62312.64	INR Sixty Two Thousand Three Hundred & Twelve and Paise Sixty Four Only
18	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	223.200	Kg	92.55	20657.16	INR Twenty Thousand Six Hundred & Fifty Seven and Paise Sixteen Only
19	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	0.120	cum	7365.50	883.86	INR Eight Hundred & Eighty Three and Paise Eighty Six Only
20	Centering and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns, etc. for mass concrete.	0.520	sqm	262.55	136.53	INR One Hundred & Thirty Six and Paise Fifty Three Only
21	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more.	11.780	Kg	75.85	893.51	INR Eight Hundred & Ninety Three and Paise Fifty One Only
22	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1 cement: 6 coarse sand)	0.340	Cum	6494.75	2208.22	INR Two Thousand Two Hundred & Eight and Paise Twenty Two Only
23	12 mm cement plaster of mix :1:6 (1 cement: 6 fine sand)	100.000	Sqm	217.70	21770.00	INR Twenty One Thousand Seven Hundred & Seventy Only
24	12 mm cement plaster finished with a floating coat of neat cement of mix : 1:4 (1 cement: 4 fine sand)	67.720	Sqm	284.75	19283.27	INR Nineteen Thousand Two Hundred & Eighty Three and Paise Twenty Seven Only
25	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 20 mm nominal dia Pipes	20.000	Mtr	259.05	5181.00	INR Five Thousand One Hundred & Eighty One Only
26	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. 15 mm nominal dia Pipes	15.000	Mtr	200.90	3013.50	INR Three Thousand & Thirteen and Paise Fifty Only
27	Providing and fixing PTMT bib cock of approved quality and colour. 15mm nominal bore, 86 mm long, weighing not less than 88 gms	5.000	Nos	95.35	476.75	INR Four Hundred & Seventy Six and Paise Seventy Five Only
28	Part(B) Shed :Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	0.820	cum	188.45	154.53	INR One Hundred & Fifty Four and Paise Fifty Three Only
29	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	0.075	cum	1844.00	138.30	INR One Hundred & Thirty Eight and Paise Thirty Only

30	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	0.670	cum	5916.00	3963.72	INR Three Thousand Nine Hundred & Sixty Three and Paise Seventy Two Only
31	12 mm cement plaster finished with a floating coat of neat cement of mix : 1:4 (1 cement: 4 fine sand)	10.500	Sqm	284.75	2989.88	INR Two Thousand Nine Hundred & Eighty Nine and Paise Eighty Eight Only
32	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-Charge) of total coated thickness 0.50mm (base metal of minimum 0.45mm thickness with total coating thickness of 0.05mm) with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in- charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	29.190	sqm	571.00	16667.49	INR Sixteen Thousand Six Hundred & Sixty Seven and Paise Forty Nine Only
33	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	155.760	Kg	92.55	14415.59	INR Fourteen Thousand Four Hundred & Fifteen and Paise Fifty Nine Only
34	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	10.900	Sqm	99.90	1088.91	INR One Thousand & Eighty Eight and Paise Ninety One Only
35	(Part-C) Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	8.290	cum	188.45	1562.25	INR One Thousand Five Hundred & Sixty Two and Paise Twenty Five Only
36	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	1.120	cum	1844.00	2065.28	INR Two Thousand & Sixty Five and Paise Twenty Eight Only
37	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	1.670	cum	5916.00	9879.72	INR Nine Thousand Eight Hundred & Seventy Nine and Paise Seventy Two Only
38	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:Cement mortar 1:6 (1 cement : 6 coarse sand)	5.590	cum	5322.15	29750.82	INR Twenty Nine Thousand Seven Hundred & Fifty and Paise Eighty Two Only
39	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6(1 cement: 6 coarse sand)	7.230	cum	6494.75	46957.04	INR Forty Six Thousand Nine Hundred & Fifty Seven and Paise Four Only
40	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level Cement mortar 1:4 (1 cement :4 coarse sand)	1.720	cum	802.35	1380.04	INR One Thousand Three Hundred & Eighty and Paise Four Only
41	Providing reinforced by organic fibres and/or inorganic synthetic fibres cement 6 mm thick corrugated sheets (as per IS: 14871) roofing up to any pitch and fixing with polymer coated J, or L hooks, bolts and nuts 8 mm dia. G.I. plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete (excluding the cost of purlins, rafters and trusses), including cutting sheets to size and shape wherever required.	8.500	Sqm	389.10	3307.35	INR Three Thousand Three Hundred & Seven and Paise Thirty Five Only
42	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	120.240	Kg	92.55	11128.21	INR Eleven Thousand One Hundred & Twenty Eight and Paise Twenty One Only
43	12 mm cement plaster of mix :1:6 (1 cement: 6 fine sand)	97.010	Sqm	217.70	21119.08	INR Twenty One Thousand One Hundred & Nineteen and Paise Eight Only
44	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	9.590	Sqm	762.85	7315.73	INR Seven Thousand Three Hundred & Fifteen and Paise Seventy Three Only
45	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	24.700	Sqm	871.30	21521.11	INR Twenty One Thousand Five Hundred & Twenty One and Paise Eleven Only
46	Providing and fixing white vitreous china pedestal type (European type/wash down type) water closet pan.	1.000	No	1986.20	1986.20	INR One Thousand Nine Hundred & Eighty Six and Paise Twenty Only
47	Providing and fixing white vitreous china water closet squatting pan (Indian type) : Orissa pattern W.C. pan of size 580x440 mm	1.000	No	2294.00	2294.00	INR Two Thousand Two Hundred & Ninety Four Only
48	Providing and fixing white vitreous china flat back or wall corner typelipped front urinal basin of 430x260x350 mm or 340x410x265 mmsizes respectively.	1.000	No	1123.65	1123.65	INR One Thousand One Hundred & Twenty Three and Paise Sixty Five Only
49	White Vitreous China Flat back wash basin size 550x400 mm with single 15 mm C.P. brass pillar tap	1.000	No	1458.10	1458.10	INR One Thousand Four Hundred & Fifty Eight and Paise Ten Only
50	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.15 mm nominal dia Pipes	1.000	Meter	336.20	336.20	INR Three Hundred & Thirty Six and Paise Twenty Only
51	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.20 mm nominal dia Pipes	5.000	Meter	399.20	1996.00	INR One Thousand Nine Hundred & Ninety Six Only

52	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.25 mm nominal dia Pipes	9.000	Meter	496.75	4470.75	INR Four Thousand Four Hundred & Seventy and Paise Seventy Five Only
53	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. (i)Single socketed pipes.	20.000	Meter	262.40	5248.00	INR Five Thousand Two Hundred & Forty Eight Only
54	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382,leaving 10 mm gap for thermal expansion.Bend 87.5°110 mm bend	5.000	Nos	114.60	573.00	INR Five Hundred & Seventy Three Only
55	Providing and fixing P.V. C.low level flushing cistern with manually controlled device (handle lever)conforming to IS :7231,with all Fittings and fixtures complete.	2.000	Nos	863.00	1726.00	INR One Thousand Seven Hundred & Twenty Six Only
56	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm. complete, including cost of cutting and making good the walls and floors: Sand Cast Iron S&S as per IS: 1729	2.000	Nos	1117.90	2235.80	INR Two Thousand Two Hundred & Thirty Five and Paise Eighty Only
57	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15mm nominal bore	1.000	No	434.40	434.40	INR Four Hundred & Thirty Four and Paise Forty Only
58	Providing and fixing PTMT bib cock of approved quality and colour.15mm nominal bore, 86 mm long, weighing not less than 88 gms	3.000	Nos	95.35	286.05	INR Two Hundred & Eighty Six and Paise Five Only
59	Providing and fixing PTMT swivelling shower, 15 mm nominal bore, weighing not less than 40 gms	1.000	Nos	92.15	92.15	INR Ninety Two and Paise Fifteen Only
60	Providing and fixing PTMT pillar cock of approved quality and colour.15 mm nominal bore, 107 mm long, weighing not less than 110 gms	1.000	Nos	156.95	156.95	INR One Hundred & Fifty Six and Paise Ninety Five Only
61	Finishing walls with water proofing cement paint of required shade :Old work (one or more coats applied @ 2.20 kg/10 sqm) over priming coat of primer applied @ 0.80 litrs/10 sqm complete including cost of Priming coat.	10.640	sqm	72.30	769.27	INR Seven Hundred & Sixty Nine and Paise Twenty Seven Only
62	White washing with Satna lime wash on walls with one coat.	20.000	sqm	9.85	197.00	INR One Hundred & Ninety Seven Only
63	Distempering with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound) content less than 50 gram/ litre, of approved brand and of required said and colour complete to give and even said.Old work (one or more coats)	60.000	sqm	38.55	2313.00	INR Two Thousand Three Hundred & Thirteen Only
64	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new work	30.000	Sqm	99.90	2997.00	INR Two Thousand Nine Hundred & Ninety Seven Only
65	Providing and fixing factory made P.V.C. door frame of size 50x47 mm with awall thickness of 5 mm, made out of extruded 5mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineer- in-Charge.	4.650	Mtr	347.45	1615.64	INR One Thousand Six Hundred & Fifteen and Paise Sixty Four Only
66	Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mm x 2) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail, paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded/ sealed to the styles & rails with 7 mm (5 mm+2 mm) thick x 15 mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per direction of Engineer-in-charge, manufacturer's specification & drawing.30 mm thick plain PVC door shutters	2.920	Nos	2092.30	6109.52	INR Six Thousand One Hundred & Nine and Paise Fifty Two Only
67	Providing and fixing unplasticised PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement: 4 coarse sand) and making good the wall etc. complete. 110 mm	5.000	Nos	234.80	1174.00	INR One Thousand One Hundred & Seventy Four Only
68	Total impact of GST for the purpose of CTC	1.000	Nos	0.00	0.00	INR Zero Only
Total in Figures					705266.26	INR Seven Lakh Five Thousand Two Hundred & Sixty Six and Paise Twenty Six Only
Quoted Rate in Figures			Select		0.00	INR Zero Only
Quoted Rate in Words	INR Zero Only					