

Validate

Print

Help

Percentage BoQ

Tender Inviting Authority: Staff Officer Civil Piparwar Area.

Name of Work : Repair of administrative block, old building and damaged boundary wall of DAV public school, Bachra under GM Unit, Piparwar Area.

.	Category of Services (To Be Selected by Department)	Category of Bidder(To Be Selected by Bidder)	To Be Entered by Department		
ITC Not Available	Works Contract	Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :		Select	18.00	0.00	0.00

PRICE SCHEDULE

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)

NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	t	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	5	6	7
1.01	PART A Repair of administrative block and old building Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gram/litre, of approved manufacturer, of required shade and colour all complete: New work (two or more coats) over and including water thinnable priming coat with cement primer having VOC content less than 50 gram/litre	1649.140	sqm	115.00	189651.10	INR One Lakh Eighty Nine Thousand Six Hundred & Fifty One and Paise Ten Only
1.02	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	2195.140	sqm	98.45	216111.53	INR Two Lakh Sixteen Thousand One Hundred & Eleven and Paise Fifty Three Only
1.03	Providing & Applying high quality acrylic modified resin based texture of Dholpur/Red sand stone Pattern with anti algae and UV resistance properties to be applied as intermediate finish in desired pattern @ 43.04 kgs/10 sqm to form film of 1- 1.5 mm thickness after scrapping and properly cleaning the surface to remove loose particles from the plaster surface, followed by top coating with Premium Acrylic Smooth exterior paint with Silicone additives of required shade by two or more coats @ 1.43 litres/10 sqm, complete as the direction of Engineer -in-Charge.	804.958	sqm	396.60	319246.34	INR Three Lakh Nineteen Thousand Two Hundred & Forty Six and Paise Thirty Four Only
1.04	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) : 25 mm thick	839.206	sqm	1373.35	1152523.56	INR Eleven Lakh Fifty Two Thousand Five Hundred & Twenty Three and Paise Fifty Six Only

1.05	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in-charge.Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)	33.568	Cum	1412.40	47411.44	INR Forty Seven Thousand Four Hundred & Eleven and Paise Forty Four Only
1.06	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar	29.760	Cum	1194.45	35546.83	INR Thirty Five Thousand Five Hundred & Forty Six and Paise Eighty Three Only
1.07	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm	92.835	sqm	1180.40	109582.43	INR One Lakh Nine Thousand Five Hundred & Eighty Two and Paise Forty Three Only
1.08	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS:15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	179.308	sqm	871.30	156231.06	INR One Lakh Fifty Six Thousand Two Hundred & Thirty One and Paise Six Only
1.09	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and for all lift, as directed by Engineer-in charge.All kinds of soil	8.420	Cum	128.05	1078.18	INR One Thousand & Seventy Eight and Paise Eighteen Only
1.10	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	1.452	Cum	1844.00	2677.49	INR Two Thousand Six Hundred & Seventy Seven and Paise Forty Nine Only
1.11	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources)	20.405	Cum	6490.90	132446.81	INR One Lakh Thirty Two Thousand Four Hundred & Forty Six and Paise Eighty One Only
1.12	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete as per the direction of Engineer in-charge.	1016.780	sqm	752.85	765482.82	INR Seven Lakh Sixty Five Thousand Four Hundred & Eighty Two and Paise Eighty Two Only
1.13	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:6.1.2 Cement mortar 1:6 (1 cement : 6 coarse sand)	1.837	Cum	5322.15	9776.79	INR Nine Thousand Seven Hundred & Seventy Six and Paise Seventy Nine Only
1.14	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :Cement mortar 1:6(1 cement: 6 coarse sand)	22.900	Cum	6494.75	148729.78	INR One Lakh Forty Eight Thousand Seven Hundred & Twenty Nine and Paise Seventy Seven Only
1.15	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:3 (1 cement :3 coarse sand)	26.250	sqm	828.35	21744.19	INR Twenty One Thousand Seven Hundred & Forty Four and Paise Nineteen Only

1.16	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	21.578	Cum	7365.50	158932.76	INR One Lakh Fifty Eight Thousand Nine Hundred & Thirty Two and Paise Seventy Six Only
1.17	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement:1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	2.084	Cum	8441.35	17591.77	INR Seventeen Thousand Five Hundred & Ninety One and Paise Seventy Seven Only
1.18	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15* landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to four five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources: 3 graded stone aggregate 20 mm nominal size derived from natural sources).	15.057	Cum	8797.65	132466.22	INR One Lakh Thirty Two Thousand Four Hundred & Sixty Six and Paise Twenty Two Only
1.19	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level Thermo-Mechanically Treated bars of grade Fe-500D or more.	3097.610	KG	75.85	234953.72	INR Two Lakh Thirty Four Thousand Nine Hundred & Fifty Three and Paise Seventy Two Only
1.20	Centering and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns, etc. for mass concrete.	60.480	sqm	262.55	15879.02	INR Fifteen Thousand Eight Hundred & Seventy Nine and Paise Two Only
1.21	Centering and shuttering including strutting, propping etc. and removal of form for Suspended floors, roofs, landings, balconies and access platform	115.063	sqm	587.10	67553.49	INR Sixty Seven Thousand Five Hundred & Fifty Three and Paise Forty Nine Only
1.22	Centering and shuttering including strutting, propping etc. and removal of form Lintels, beams, plinth beams, girders, bressumers and cantilevers.	49.550	sqm	470.70	23323.19	INR Twenty Three Thousand Three Hundred & Twenty Three and Paise Eighteen Only
1.23	Centering and shuttering including strutting, propping etc. and removal of form for Columns, Pillars, Piers, Abutments, Posts and Struts.	33.750	sqm	621.80	20985.75	INR Twenty Thousand Nine Hundred & Eighty Five and Paise Seventy Five Only
1.24	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	163.200	sqm	77.95	12721.44	INR Twelve Thousand Seven Hundred & Twenty One and Paise Forty Four Only
1.25	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. Fixed to steel windows by welding	421.840	KG	145.60	61419.90	INR Sixty One Thousand Four Hundred & Nineteen and Paise Ninety Only
1.26	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new work	61.060	KG	99.90	6099.89	INR Six Thousand & Ninety Nine and Paise Eighty Nine Only

1.27	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing I paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	364.440	sqm	367.10	133785.92	INR One Lakh Thirty Three Thousand Seven Hundred & Eighty Five and Paise Ninety Two Only
1.28	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)	224.505	KG	462.05	103732.54	INR One Lakh Three Thousand Seven Hundred & Thirty Two and Paise Fifty Four Only
1.29	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): 21.3.1 With float glass panes of 4.0 mm thickness (weight not less than 10kg/sqm)	501.948	sqm	824.65	413931.42	INR Four Lakh Thirteen Thousand Nine Hundred & Thirty One and Paise Forty Two Only
1.30	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	48.300	sqm	1575.70	76106.31	INR Seventy Six Thousand One Hundred & Six and Paise Thirty One Only
1.31	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size, with top and bottom rail of Tiron 40x40x6mm, with 40mm dia steel pulleys, complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.	8.640	sqm	7450.80	64374.91	INR Sixty Four Thousand Three Hundred & Seventy Four and Paise Ninety One Only
1.32	Grading roof for water proofing treatment with Cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size)	4.280	Cum	6616.35	28317.98	INR Twenty Eight Thousand Three Hundred & Seventeen and Paise Ninety Eight Only

1.33	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer 3 mm thick water proofing membrane, black finished reinforced with non-woven polyester matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufacture of density at 25°C, 0.87-0.89 kg/ litre and viscosity 70-160 cps. Over the primer coat the layer of membrane shall be laid using Butane Torch and sealing all joints etc, and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under : Joint strength in longitudinal and transverse direction at 23°C as 650/ 450N/ 5cm. Tear strength in longitudinal and transverse direction as 300/ 250N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane : 3 mm thick	161.354	sqm	469.25	75715.36	INR Seventy Five Thousand Seven Hundred & Fifteen and Paise Thirty Six Only
1.34	Providing and fixing pre-coated galvanised iron profile sheets(size, shape and pitch of corrugation as approved by Engineer-in-Charge) of total coated thickness 0.50mm (base metal of minimum 0.45mm thickness with total coating thickness of 0.05mm)with zinc coating 120 grams per sqm as per IS:277, in 240m pastel grade, 5-7micron sepxy primer on both side of the sheet and polyester topcoat 15-18microns. Sheet should have protective guard film of 25microns minimum to avoid scratches during transportation and should be supplied in single length upto 12metre or as desired by Engineer-in- charge. The sheet shall be fixed using self drilling/self tapping screws of size (5.5x 55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	108.000	sqm	571.00	61668.00	INR Sixty One Thousand Six Hundred & Sixty Eight Only
1.35	Extra for providing and fixing wind ties of 40x 6 mm flat iron section. metre 138.75	24.000	MTR	138.75	3330.00	INR Three Thousand Three Hundred & Thirty Only
1.36	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore	20.000	each	376.95	7539.00	INR Seven Thousand Five Hundred & Thirty Nine Only
1.37	Providing and fixing C.P. brass stop cock of approved quality conforming to IS:8931 : 15 mm nominal bore	15.000	each	434.40	6516.00	INR Six Thousand Five Hundred & Sixteen Only
1.38	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :25 nominal bore	8.000	each	462.15	3697.20	INR Three Thousand Six Hundred & Ninety Seven and Paise Twenty Only
1.39	Providing and fixing white vitreous china flat back half stall urinal of size 580x380x350mm with white PVC automatic flushing cistern, with fittings, standard size C.P. brass flush pipe, spreaders with unions and clamps (all in C.P. brass) with waste fitting as per IS:2556, C.I. trap with outlet grating and other couplings in C.P. brass, including painting of fittings and cutting and making good the walls and floors wherever required :Single half stall urinal with 5 litre P.V.C. automatic flushing cistern	8.000	each	8003.45	64027.60	INR Sixty Four Thousand & Twenty Seven and Paise Sixty Only

1.40	Providing and fixing water closet squatting pan(Indian type W.C.pan) with 100 mm sand cast Iron Por S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	10.000	each	4774.45	47744.50	INR Forty Seven Thousand Seven Hundred & Forty Four and Paise Fifty Only
1.41	Providing and fixing PTMT pillar cock of approved quality and colour 15 mm nominal bore, 125 mm long foam flow, weighing not less than 120 gms	6.000	each	168.55	1011.30	INR One Thousand & Eleven and Paise Thirty Only
1.42	White Vitreous China Flat back wash basin size 550x400 mm with single 15 mm C.P. brass pillar tap	10.000	each	1458.10	14581.00	INR Fourteen Thousand Five Hundred & Eighty One Only
1.43	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank.	4000.000	per ltr	8.40	33600.00	INR Thirty Three Thousand Six Hundred Only
1.44	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS:13592 Type A, including jointing with seal ring conforming to IS:5382, leaving 10mm gap for thermal expansion, (i) Single socketed pipes. 110 mm diameter.	45.000	mtr	262.40	11808.00	INR Eleven Thousand Eight Hundred & Seven and Paise One Hundred Only
1.45	Providing and fixing on wall face unplasticised- PVC moulded fittings/accessories for unplasticised Rigid PVC rainwater pipes conforming to IS :13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. 110 mm bend.	60.000	each	114.60	6876.00	INR Six Thousand Eight Hundred & Seventy Six Only
1.46	Providing and fixing unplasticised PVC pipe clips of approved design to unplasticised-PVC rainwater pipes by means of 50x50x50mm hardwood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement:4 coarse sand) and making good the wall etc. complete 110 mm.	60.000	each	234.80	14088.00	INR Fourteen Thousand & Eighty Eight Only
1.47	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - 15 mm nominal dia Pipes	45.000	mtr	200.90	9040.50	INR Nine Thousand & Forty and Paise Fifty Only
1.48	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - 20 mm nominal dia Pipes metre	75.000	mtr	259.05	19428.75	INR Nineteen Thousand Four Hundred & Twenty Eight and Paise Seventy Five Only

1.49	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - 25 mm nominal dia Pipes metre	45.000	mtr	331.50	14917.50	INR Fourteen Thousand Nine Hundred & Seventeen and Paise Fifty Only
1.50	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50metres lead.	279.450	sqm	32.00	8942.40	INR Eight Thousand Nine Hundred & Forty Two and Paise Forty Only
1.51	12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)	558.716	sqm	231.05	129091.33	INR One Lakh Twenty Nine Thousand & Ninety One and Paise Thirty Three Only
1.52	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with : 12.5 mm thick tapered edge gypsum moisture resistant board	153.500	sqm	1037.85	159309.98	INR One Lakh Fifty Nine Thousand Three Hundred & Nine and Paise Ninety Seven Only
1.53	Filling available excavated earth (excluding rock) in trenches, plinth.sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead upto 50m and for all lift	2.780	cum	114.40	318.03	INR Three Hundred & Eighteen and Paise Three Only
1.54	Finishing walls with Acrylic Smooth exterior paint of required shade . New work (Two or more coat applied @ 1.67 ILO 0 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sarM	546.000	sqm	115.85	63254.10	INR Sixty Three Thousand Two Hundred & Fifty Four and Paise Ten Only

1.55	Applying vinyl artistic painting of approved design, over the wall surface with approved material all complete, as per direction of EIC	805.895	sqft	139.38	112325.65	INR One Lakh Twelve Thousand Three Hundred & Twenty Five and Paise Sixty Five Only
1.56	Carriage of materials. By Mechanical Transport including loading,unloading and stacking. Lime, moorum, building rubbish Lead - 1 km	175.000	cum	110.36	19313.00	INR Nineteen Thousand Three Hundred & Thirteen Only
1.57	PART B Repair of damaged boundary wall at backside of DAV public school Bachra Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge	14.156	Cum	1194.45	16908.63	INR Sixteen Thousand Nine Hundred & Eight and Paise Sixty Three Only
1.58	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge.All kinds of soil	73.253	Cum	128.05	9380.05	INR Nine Thousand Three Hundred & Eighty and Paise Five Only
1.59	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	5.705	Cum	1844.00	10520.02	INR Ten Thousand Five Hundred & Twenty and Paise Two Only
1.60	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources)	11.410	Cum	5167.75	58964.03	INR Fifty Eight Thousand Nine Hundred & Sixty Four and Paise Three Only
1.61	P/L specified grade of RCC excluding centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 -coarse sand - 20 mm stone aggregate)	70.846	Cum	7365.50	521816.21	INR Five Lakh Twenty One Thousand Eight Hundred & Sixteen and Paise Twenty One Only
1.62	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement: 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	52.182	Cum	8441.35	440486.53	INR Four Lakh Forty Thousand Four Hundred & Eighty Six and Paise Fifty Three Only
1.63	Reinforcement for R.C.C. work all complete. Thermo-Mechanically Treated bars of grade Fe-500D or more.	11072.610	KG	75.85	839857.47	INR Eight Lakh Thirty Nine Thousand Eight Hundred & Fifty Seven and Paise Forty Seven Only
1.64	Centering and shuttering including strutting, propping etc. and removal of form work for: Foundations, footings, bases for columns	90.270	sqm	262.55	23700.39	INR Twenty Three Thousand Seven Hundred and Paise Thirty Nine Only
1.65	Centering and shuttering including strutting, propping etc. and removal of form for: Walls any thickness) including attached pilasters, butteresses, plinth and string courses etc.	523.800	sqm	538.75	282197.25	INR Two Lakh Eighty Two Thousand One Hundred & Ninety Seven and Paise Twenty Five Only

1.66	Providing weep holes in Brick masonry/Plain/ Reinforced concrete abutment, wing wall/return wall with 100 mm dia AC pipe, extending through the full width of the structure with slope of 1V :20H towards drawing face. Complete as per drawing and Technical specifications	156.000	each	143.00	22308.00	INR Twenty Two Thousand Three Hundred & Eight Only
1.67	Filling available excavated earth (excluding rock) in trenches, plinth. sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and for all lift	24.170	sqm	114.40	2765.05	INR Two Thousand Seven Hundred & Sixty Five and Paise Five Only
1.68	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 5 km for all lifts, complete as per directions of Engineer-in-charge.	93.236	cum	321.70	29994.02	INR Twenty Nine Thousand Nine Hundred & Ninety Four and Paise Two Only
1.69	Total impact of GST for the purpose of CTC	1.000	Nos	0.00	0.00	INR Zero Only
Total in Figures					8027457.43	INR Eighty Lakh Twenty Seven Thousand Four Hundred & Fifty Seven and Paise Forty Three Only
Quoted Rate in Figures			Select		0.00	INR Zero Only
Quoted Rate in Words		INR Zero Only				